
KERPEN DATACOM

MegaLine® F10-115 S/F Dca

KS-02YSCH 4 x 2 x AWG 23/1 PIMF

Category 7_A **S_3 P_4 A_4 C_4 E_5**






Illustration similar

Construction

Conductor	bare copper wire, AWG 23/1	Twisting	4 pairs
Insulation	cellular-PE, Core-Ø: nominal value 1.40 mm	Overall screen	tinned copper wire braid
Colour code	WH/BU, WH/OG, WH/GN, WH/BN	Outer sheath	Halogen free flame retardant compound (FRNC)
Element	cores to pair		
Pair shielding	aluminium-bonded polyester tape	Colour	Colza yellow

Cable marking

KERPEN DATACOM Made in Germany MegaLine F10-115 S/F 4P LSOH Cat.7A 4PPoE 90W Dca DoP: CDESK0000005 $BA-Nr.$ $m-sign.$

Fire Behaviour

Fire performance	EN 50575 / EN 50399
Circuit integritiy	[-]
Flame retardancy	IEC 60332-3-24
Halogen-free	IEC 60754-1, IEC 60754-2
Acidity	IEC 60754-2
Smoke density	IEC 61034-2
Fire load (approx.)	0.61 MJ/m

S	1 IEC 60332-2-2	2 IEC 60332-1-2	**3 IEC 60332-3-24**	4 EFP Grade 1	5 EFP Grade 2

Security (fire behaviour)

Performance

better than Category 7A acc. to EN 50288 and IEC 61156 excellent NEXT, exzellent screen properties (pair- and overall screen), low Skew

Bandwidth (max.) 1000 MHz

P	1 >class E >250MHz	2 >class E >500MHz	3 >class F >600MHz	**4 >class F >1000MHz**	5 >class G >1200MHz

Performance (class, bandwidth)

Applications

Installation cable for generic cabling systems acc. to ISO/IEC 11801 and EN 50173 (3nd edition). Ideal for all applications of class D up to FA Multimedia (Video, Data, Voice) >10 GbE acc. to IEEE 802.3 an, Cable sharing, VoIP, PoE/PoE+/4PPoE

A	1 >100 MbE	2 > 1GbE	3 bis 10 GbE	**4 >10 GbE**	5 >10 GbE / TV

Application (Ethernet, TV)

Mechanical characteristics (cable)

Bending radius (static) (min.)	4x outer-Ø
Bending radius (dynamic) (min.)	8x outer-Ø
Tensile strength	110 N
Crush resistance (long term)	1000 N/100mm
Impact strength (quantity of impacts)	10

C	1 AWG 27	2 AWG 26/25	3 AWG 24	**4 AWG 23**	5 AWG 22

Construction (conductor size, tensile strengh)

Electromagnetic behaviour

Coupling resistance @ 10 MHz (nom.)	5 mΩ/m
Screen attenuation (nom.)	70 dB
Coupling attenuation (nom.)	85 dB
Segregation class according to EN 50174-2	d

E	1 > 40 dB	2 > 50 dB	3 > 60 dB	4 > 70 dB	**5 > 80 dB**

EMC (coupling attentuation)

Forwarding to third parties only with the approval of KERPEN DATACOM GmbH
We reserve the right to make technical modifications; typographical errors and mistakes excepted.

KERPEN DATACOM

MegaLine® F10-115 S/F Dca

KS-02YSCH 4 x 2 x AWG 23/1 PIMF

Category 7_A **S_3 P_4 A_4 C_4 E_5**

Electrical properties at 20°C

DC resistance (max.)	75 Ω/km
Insulation resistance (min.)	5 GΩ x km
Operating capacity (approx.)	42 pF/m
Capacitive coupling (e) (approx.)	1100 pF/km
Signal velocity (approx.)	0.8 x c
Phase delay	420 ns/100m
Skew @ 100 MHz (approx.)	5 ns/100m
Characteristic impedance @ 100 MHz	100 +/- 5 Ω
Test voltage	1000 V
Operating voltage (max.)	125 V

Thermal characteristics (cable)

Transport / storage	-20 °C up to +60 °C
During installation	0 °C up to +50 °C
After installation	-20 °C up to +60 °C

Chemical characteristics

Conform to RoHS and REACH

Frequenz MHz	Attenuation dB/100m		NEXT dB		PSNEXT dB		ACR-N dB@100m		PSACR-N dB@100m		ACR-F dB@100m		PSACR-F dB@100m		RL dB	
	typ.	Cat.7_A max.*	typ.	Cat.7_A min.*	typ.	Cat.7_A min.*	typ.	Cat.7_A min.*	typ.	Cat.7_A min.*	typ.	Cat.7_A min.*	typ.	Cat.7_A min.*	typ.	Cat.7_A min.*
1	1,9	2,1	105	78	102	75	104	75,9	101	72,9	98	78	95	75	26,6	-
10	4,8	5,8	105	78	102	75	104	75,9	101	72,9	98	78	95	75	35,3	25,0
100	16,3	18,5	105	75	102	72	89	56,9	86	53,9	89	65	86	62	39,6	20,1
200	24,3	26,5	105	71	102	68	81	44,4	78	41,4	82	59	79	56	36,0	18,0
250	27,5	29,7	105	69	102	66	78	39,7	75	36,7	79	57	76	54	34,0	17,3
500	37,9	42,8	100	65	97	62	62	22,1	59	19,1	67	51	64	48	29,0	17,3
600	42,4	47,1	95	64	92	61	53	16,6	50	13,6	60	50	57	47	25,4	17,3
700	47,2	51,1	95	63	92	60	48	11,6	45	8,6	57	48	54	45	24,6	16,6
800	50,3	54,9	93	62	90	59	43	7,0	40	4,0	53	47	50	44	23,5	16,1
900	54,6	58,5	90	61	87	58	35	2,6	32	-0,4	49	46	46	43	22,6	15,5
1000	58,0	61,9	88	60	85	57	30	-1,5	27	-4,5	44	45	41	42	21,5	15,1

* EN 50288-9-1(2013) / IEC 61156-5(2020)

Standards, certificates and approvals

Conformity	to CPR (EU/305/2011) acc. to LVD (2014/35/EU)
Link Performance	KERPEN DATACOM MegaLine® systems and further commercial plug-inn connector
Inspection certificate	acc. to DIN 55350-18-4.2.1 bzw. EN 10204

Part number	Weight	Copper weight	Outer Ø approx.	PU (pieces)	Colour
KD7D67D3Y090100	56 kg/km	37 kg/km	7.2 mm	1	Colza yellow

Packaging

1000 m cable drum

Forwarding to third parties only with the approval of KERPEN DATACOM GmbH
We reserve the right to make technical modifications; typographical errors and mistakes excepted.