
MegaLine® E5-60 U/U Dca

KS-02YSH 4 x 2 AWG 23/1

Category 6_A **S_3 P_2 A_3 C_4 E_1**






Illustration similar

Construction

Conductor	bare copper wire, 0.56 mm Ø	Twisting	4 pairs
Insulation	cellular-PE, Core-Ø: nominal value 1.28 mm	Overall screen	unscreened
Colour code	WH/BU, WH/OG, WH/GN, WH/BN	Outer sheath	Halogen free flame retardant compound (FRNC)
Element	cores to pair		
Pair shielding	polyester protection tape, segmented design	Colour	Colza yellow

Cable marking

KERPEN DATACOM Made in Germany MegaLine E5-60 U/U 4P LSOH Cat.6A 600MHz 10G 4PPoE 90W Dca DoP: CDESK0000100 $BA-Nr.$ $m-sign.$

Fire Behaviour

Fire performance	EN 50575 / EN 50399
Flame retardancy	IEC 60332-3-24
Halogen-free	IEC 60754-1/2
Acidity	IEC 60754-2
Smoke density	IEC 61034-2
Fire load (approx.)	0.53 MJ/m

S	1	2	3	4	5
	IEC 60332-2-2	IEC 60332-1-2	**IEC 60332-3-24**	EFP Grade 1	EFP Grade 2

Security (fire behaviour)

Performance

better than Category 6A acc. to EN 50288 and IEC 61156

Bandwidth (max.) 600 MHz

P	1	2	3	4	5
	>class E >250MHz	**>class E >500MHz**	>class F >600MHz	>class F >1000MHz	>class G >1200MHz

Performance (class, bandwidth)

Applications

Installation cable for generic cabling systems acc. to ISO/IEC 11801 and EN 50173 (3nd edition). Ideal for all applications of class D up to EA up to 10 GbE acc. to IEEE 802.3 an, Cable sharing, VoIP, 4PPoE (90 W).

A	1	2	3	4	5
	>100 MbE	> 1GbE	**bis 10 GbE**	>10 GbE	>10 GbE / TV

Application (Ethernet, TV)

Mechanical characteristics (cable)

Bending radius (static) (min.)	4x outer-Ø
Bending radius (dynamic) (min.)	8x outer-Ø
Tensile strength	110 N
Crush resistance (long term)	1000 N/100mm
Impact strength (quantity of impacts)	10

C	1	2	3	4	5
	AWG 27	AWG 26/25	AWG 24	**AWG 23**	AWG 22

Construction (conductor size, tensile strengh)

Electromagnetic behaviour

Coupling attenuation (nom.)	45 dB
Segregation class according to EN 50174-2	b

E	1	2	3	4	5
	> 40 dB	> 50 dB	> 60 dB	> 70 dB	> 80 dB

EMC (coupling attentuation)

Forwarding to third parties only with the approval of KERPEN DATACOM GmbH
We reserve the right to make technical modifications; typographical errors and mistakes excepted.

MegaLine® E5-60 U/U Dca

KS-02YSH 4 x 2 AWG 23/1

Category 6_A **S_3 P_2 A_3 C_4 E_1**

Electrical properties at 20°C

DC resistance (max.)	82 Ω/km
Insulation resistance (min.)	5 GΩ x km
Operating capacity (approx.)	42 pF/m
Capacitive coupling (e) (approx.)	1100 pF/km
Signal velocity (approx.)	0.8 x c
Phase delay	420 ns/100m
Skew @ 100 MHz (approx.)	7 ns/100m
Characteristic impedance @ 100 MHz	100 +/- 5 Ω
Test voltage	1000 V
Operating voltage (max.)	125 V

Thermal characteristics (cable)

Transport / storage	-20 °C up to +60 °C
During installation	0 °C up to +50 °C
After installation	-20 °C up to +60 °C

Chemical characteristics

Conform to RoHS and REACH

Frequenz MHz	Attenuation dB/100m		NEXT dB		PSNEXT dB		ACR-N dB@100m		PSACR-N dB@100m		ACR-F dB@100m		PSACR-F dB@100m		RL dB	
	typ.	$Cat.6_A$ max.*	typ.	$Cat.6_A$ min.*	typ.	$Cat.6_A$ min.*	typ.	$Cat.6_A$ min.*	typ.	$Cat.6_A$ min.*	typ.	$Cat.6_A$ min.*	typ.	$Cat.6_A$ min.*	typ.	$Cat.6_A$ min.*
1	2,0	2,1	78	75,3	75	72,3	76	73,2	73	70,2	75	68	72	65	-	-
10	5,8	5,9	65	60,3	62	57,3	59,2	54,4	56,2	51,4	55	48	52	45	30	25,0
100	18,7	19,1	50	45,3	47	42,3	31,3	26,2	28,3	23,2	40	28	37	25	25	20,1
200	27,0	27,6	45	40,8	42	37,8	18	13,2	15	10,2	33	22	30	19	23	18,0
250	29,9	31,1	43	39,3	40	36,3	13,1	8,2	10,1	5,2	30	20	27	17	20	17,3
300	33,6	34,3	42	38,1	39	35,1	8,4	3,8	5,4	0,8	29	19	26	16	20	17,3
450	41,9	42,7	40	35,5	37	32,5	-1,9	-7,2	-4,9	-10,2	25	15	22	12	20	17,3
500	44,4	45,3	39	34,8	36	31,8	-5,4	-10,5	-8,4	-13,5	23	14	20	11	20	17,3
600	49,1	-	37	-	34	-	-12,1	-	-15,1	-	20	-	17	-	18	-

* EN 50288-4-1(2014) / IEC 61156-5(2020)

Standards, certificates and approvals

Conformity	to CPR (EU/305/2011) acc. to LVD (2014/35/EU)
Link Performance	KERPEN DATACOM MegaLine® systems and further commercial plug-inn connector
Inspection certificate	acc. to DIN 55350-18-4.2.1 bzw. EN 10204

Part number	Weight	Copper weight	Outer Ø approx.	PU (pieces)	Colour
KD7D15D3Y010050	46 kg/km	20 kg/km	7 mm	1	Colza yellow

Forwarding to third parties only with the approval of KERPEN DATACOM GmbH
We reserve the right to make technical modifications; typographical errors and mistakes excepted.